

P.C.B. FUSE CLIP

3AG / GMA P.C.B. FUSE CLIP

RoHS



3AG P.C.B. FUSE CLIP

FC-01

Specifications :

- Electrical: Rated for currents up to 15A.
- Material: Spring brass, Thickness 0.5mm.
- Finish: Tin-plated.
- Ear type, with axil and direction lags.
- Applicable Fuse: 6.35 x 32 & 6.35 x 30mm.



GMA P.C.B. FUSE CLIP

FC-04

Specifications :

- Electrical: Rated for currents up to 10A.
- Material: Spring brass, Thickness 0.35mm.
- Finish: Tin-plated.
- Ear type, with axil and direction lags.
- Applicable Fuse: 5.2 x 20mm.

ATY-N P.C.B. FUSE CLIP



FC-06

Specifications :

- Electrical: Rated for currents up to 15A.
- Material: Spring brass, Thickness 0.35mm.
- Finish: Tin-plated.
- Applicable Fuse: ATY-N (ATC, ATO)



FC-06 A

Specifications :

- Electrical: Rated for currents up to 15A.
- Material: Spring brass, Thickness 0.35mm.
- Finish: Tin-plated.
- Applicable Fuse: ATY-N (ATC, ATO)

MIN-N P.C.B. FUSE CLIP



FC-07

Specifications :

- Electrical: Rated for currents up to 15A.
- Material: Spring brass, Thickness 0.3mm.
- Finish: Tin-plated.
- Applicable Fuse: MIN-N (ATM, MINI)



FC-08

Specifications :

- Electrical: Rated for currents up to 15A.
- Material: Spring brass, Thickness 0.3mm.
- Finish: Tin-plated.
- Applicable Fuse: MIN-N (ATM, MINI)